

Technical Data

	Bugatti 120	Bugatti 300	Bugatti 400
Output Power:	120 W / 4 Ohm, 70 W / 8 Ohm	300 W / 4 Ohm, 160 W / 8 Ohm	400 W / 4 Ohm, 210 W / 8 Ohm
Mono bridged:	240 W / 8 Ohm, 140 W / 16 Ohm	600 W / 8 Ohm, 320 W / 16 Ohm	800 W / 8 Ohm, 420 W / 16 Ohm
Distortion (THD):		< 0,1%, 20 Hz - 20 kHz	
Intermodulation (CCIF):		< 0,05%, 20 Hz - 20 kHz	
Frequency range:		15 Hz - 20 kHz +/- 0,1dB	
Noise figure:		> 103 dB, A-weighted	
Input impedance:		20 KOhm	
Input connectors:		2 XLR in parallel for each channel	
XLR connection:		1 ground, 2 +, 3 -	
Outputs:		Binding posts	
Housing:		19", 3 units	
Depth-in case:		34 cm (13.4")	
Depth-all over:		38 cm (15")	
Weight:	18 kg (39.5 lbs)	27 kg (59 lbs)	29 kg (63.5 lbs)
Power requirement:	230 V / 2 A slo 117 V / 4 A slo 100 V / 5 A slo	230 V / 3,15 A slo 117 V / 6,3 A slo 100 V / 7 A slo	230 V / 4 A slo 117 V / 8 A slo 100 V / 9 A slo