

Technical Data

Solid state class D powered bass amplifier, 19" rack mountable, 2 rackspaces high.

Inputs

- 1 Jack ¼" A for basses with normal output level, 3 MΩ
- 1 Jack ¼" B for basses with higher output, additional pre-damping control, 4.7 MΩ

Equalization

Bass	+/- 15dB	60Hz
Low	+/- 12dB	130Hz
Mid	+/- 8dB	550Hz
High	+/- 12dB	4.2kHz
Treble	+/- 15dB	12kHz

Outputs

- 1 Tune Send Jack ¼"
- 1 Balanced DI Out XLR, pin 1 ground, pin 2 signal+, pin 3 signal -
- 2 Speakers Speakon, pin 1+ and 2+ signal hot, pin 1- and 2- signal cold
- 1 Phones Stereo-jack ¼"

Effects

- 1 Parallel Loop, post eq, with mix feature (0-100%) and footswitch activation, also usable as MP3 input (stereo input ¼" jack).

Switches

- 1 Input A/B (activates Input A or B)
- 1 Tune (cancels all outputs without Tune Send)
- 1 Eq On
- 1 Effect On
- 1 Power On
- 1 Ground Lift
- 1 DI pre/post Eq
- 1 Loop Return mono / MP3 In stereo
- 1 Footswitch jack Tune On
- 1 Footswitch jack Effect On

Special Features

- LED Peak Indicators for Pre-Amp and Power Amp
- LED Indicators for all switch functions
- Built in A/B box with separate damping control for Input B

Output Power:	650 watts@4 Ω, 340 watts@8 Ω DIP-switches ON or 650 watts@2.7 Ω, 450 watts@4 Ω, 240 watts @ 8 Ω DIP-switches OFF
Frequency Range:	20 Hz to 20 KHz -1dB
Power Requirement:	200-260 V AC, 5A slo / 100-130V AC, 8A slo
Dimensions:	320 x 88 x 260 mm (12.6 x 3.5 x 10.2")
Weight:	5 kg (11 lbs)