

Technical Data

Solid state class D powered bass amplifier, 19" rack mountable, 1.5 rackspaces high.

Inputs

1 Jack ¼" for all instruments, 1MΩ

Equalization

Bass	+15dB	60Hz, -15dB	20Hz
Low Mid	±12dB	150Hz / 240 Hz	
Mid	±12dB	770Hz / 1.5 KHz	
Treble	±15dB	8kHz	

Outputs

1 Tuner Out	Jack ¼"
1 Effect Loop Send	Jack ¼"
1 Balanced DI Out	XLR, pin 1 ground, pin 2 signal+, pin 3 signal -, switchable level
2 Speakers	Speakon, pin 1+ and 2+ signal hot, pin 1- and 2- signal cold
1 Phones	Stereo-jack ¼"

Effects

1 Parallel Loop, post eq, with mix feature (0-100%) and footswitch activation, also usable as MP3 input (stereo input ¼" jack).

Switches

- 1 -20 dB (input signal damping)
- 1 Tune (cancels all outputs without Tuner Out)
- 1 Drive On
- 1 Voice On
- 2 Mid H/L (switch the corresponding frequencies of the mid pots)
- 1 Eq On
- 1 Effect On
- 1 Ground Lift
- 1 DI pre/post Eq
- 1 Loop Return mono / MP3 In stereo
- 1 Footswitch jack Tune On
- 1 Footswitch jack Effect Loop On
- 1 Footswitch jack Drive On
- 1 Impedance 4/2.7 Ohm (minimum output impedance)
- 1 Power On

Special Features

- Drive section with Voice filter
- LED Overdrive indicator for pre-amp
- LED Indicators for switch functions

Output Power:	700 watts@4 Ω, 380 watts@8 Ω Impedance-switch Off or 700 watts@2.7 Ω, 470 watts@4 Ω, 240 watts @ 8 Ω Impedance-switch On
Frequency Range:	20 Hz to 20 KHz -1dB
Power Requirement:	200-260 V AC, 4A slo / 100-130V AC, 6.3A slo
Dimensions:	320 x 63 x 260 mm (12.6 x 2.5 x 10.2")
Weight:	3.4 kg (7.5 lbs)